


[Print Preview](#)

[Show Metric](#)

**1076A**



**Multi-Conductor - 300V Power-Limited Tray Cable**

20 AWG pairs stranded (7x28) bare copper conductors, twisted pairs, PVC insulation, individually shielded plus an overall Beldfoil shield (100% coverage), PVC jacket.

**For more Information  
Please call**

**1-800-Belden1**



[Click here for Certificate](#)

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1076A 0107500	7,500 FT	825.000 LB	BLACK	C Z	4 SH PR #20 + 1 #22 PVC FS PVC

**Notes:**

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

## Physical Characteristics (Overall)

### Conductor

**AWG:**

# Conductors	# Pairs	AWG	Stranding	Conductor Material
	4	20	7x28	BC - Bare Copper
1		22	7x30	BC - Bare Copper

**Total Number of Conductors:**

9

### Insulation

**Insulation Material:**

Insulation Material	Dia. (in.)
PVC - Polyvinyl Chloride	.068

### Inner Shield

**Inner Shield Material:**

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

**Inner Shield Drain Wire AWG:**

AWG
22

Inner Shield Drain Wire Stranding: 7x30  
 Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

**Outer Shield****Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.053

Outer Jacket Ripcord: Yes

**Overall Cable****Overall Cabling Lay Length & Direction:**

Direction
Left-hand Lay

Overall Nominal Diameter: 0.411 in.

**Pair****Pair Color Code Chart:**

Number	Color
1	Black & White and Numbered 1
2	Black & White and Numbered 2
3	Black & White and Numbered 3
4	Black & White and Numbered 4
Communication Wire	Orange

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -30°C To +105°C  
 UL Temperature Rating: 105°C  
 Bulk Cable Weight: 100 lbs/1000 ft.

Max. Recommended Pulling Tension:	171 lbs.
Min. Bend Radius/Minor Axis:	4.500 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMG, ITC-ER, PLTC-ER
CEC/C(UL) Specification:	CMG
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	UL1685 FT4 Loading
C(UL) Flame Test:	FT4
IEEE Flame Test:	1202

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Burial:	Yes
Sunlight Resistance:	Yes

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Surface Printing (Overall)

## Electrical Characteristics (Overall)

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

9.5

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.5

### Max. Operating Voltage - UL:

Voltage

300 V RMS (PLTC

CMG)

150 V RMS (ITC)

**Max. Recommended Current:**

**Current**

4.2 Amps per conductor @ 25°C

Close

Revision Number: 2    Revision Date: 01-20-2015

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.