

[Print Preview](#)

[Show Metric](#)

**30814**

**Hook-up/Lead - UL AWM Style 3070**

UL Recognizes finer stands on the 150°C rated wire. The Silicone insulation strips clean and easy. Recommended for high-temperature applications. This wire can be used with Class 130(B), 155(F) or 180(H) insulation systems.



**For more Information  
Please call**

**1-800-Belden1**



[Click here for Certificate](#)

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
30814 009500	500 FT	12.000 LB	WHITE	F	#14 SIL GL BRD 150C 600V
30814 010500	500 FT	12.000 LB	BLACK	F	#14 SIL GL BRD 150C 600V

**Notes:**

F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'

## Physical Characteristics (Overall)

### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
1	14	41x30	TC - Tinned Copper

**Total Number of Conductors:**

1

### Insulation

**Insulation Material:**

Insulation Material	Wall Thickness (in.)
Silicone with Lacquered Glass Braid Covering	.030

### Overall Insulation

### Overall Cable

Overall Nominal Diameter: 0.164 in.

### Mechanical Characteristics (Overall)

Non-UL Temperature Rating: 150°C  
Recommended Maximum Baking Cycles: 24 Hours @ 410°F (210°C)

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

UL AWM Style: 3070  
UL Rating: 600 V, 150°C  
CSA Rating: 600 V, 150°C  
CSA Type: SEWF-2  
EU Directive 2011/65/EU (ROHS II): Yes  
EU CE Mark: Yes  
EU Directive 2000/53/EC (ELV): Yes  
EU Directive 2002/95/EC (RoHS): Yes  
EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004  
EU Directive 2002/96/EC (WEEE): Yes  
EU Directive 2003/11/EC (BFR): Yes  
CA Prop 65 (CJ for Wire & Cable): Yes  
MII Order #39 (China RoHS): Yes

#### Plenum/Non-Plenum

Plenum (Y/N): No

Close

Revision Number: 1    Revision Date: 05-14-2007

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the

best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.