



Product information ACA11-EEC

Industrial Ethernet: System Accessories: Adapter cable: ACA11-EEC
<https://e-catalog.beldensolutions.com:443/link/57078-24455-24544-24546-40943/en/conf/ui/istate>

Name	ACA11-EEC
	
	The ACA 11 auto-configuration adapter saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and quickly replaced. The ACA 11 is supported by the following Switch families: RS20, RS30, RS40, MS20, MS30
Delivery informations	
Availability	available
Product description	
Description	The ACA 11 auto-configuration adapter saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and quickly replaced. The ACA 11 is supported by the following Switch families: RS20, RS30, RS40, MS20, MS30
Type	ACA11-EEC
Order No.	943 751-002
More Interfaces	
To the RS232 interface on the switch	RJ11 connector
To the RS232 interface on the PC or notebook	n/a
To the USB interface on the switch	n/a
Power requirements	
Operating voltage	via the RS232 interface on the switch
Service	
Diagnostics	writing to ACA, reading from ACA, writing/reading not OK; (display using LEDs on the switch)
Configuration	via the RS232 interface of the switch and via SNMP/Web
Ambient conditions	
Operating temperature	-40 °C ... 70 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	10 % ... 95 %
MTBF	370.9 years (MIL-HDBK-217F)
Mechanical construction	
Dimensions (W x H x D)	90 mm x 27 mm x 12 mm
Mounting	plug-in module
Weight	35 g
Protection class	IP40
Cable length	31.5 cm
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 g, 10 Hz - 150 Hz, 30 cycles
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m
EMC emitted immunity	
EN 55022	EN 55022
Approvals	
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd
Safety of information technology equipment	cUL 60950-1 (pending)
Safety of industrial control equipment	cUL 508
Scope of delivery and accessories	
Scope of delivery	device, operating manual



HIRSCHMANN

A **BELDEN** BRAND

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.