



Product information OpenOCTOPUS Fast Ethernet - OCTOPUS OS20-000900T5T5TAFBHH

Industrial Ethernet:Waterproof IP67/IP54 Switches:OpenOCTOPUS:OpenOCTOPUS Fast Ethernet

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49850-351255-400977/en/OS20-000900T5T5TAFBHH08.0/uistate>

Name OpenOCTOPUS Fast Ethernet



Managed IP 65 / IP 67 switch in accordance with IEEE 802.3, store-and-forward-switching, software layer 2 Basic, electrical Fast-Ethernet (10/100 MBit/s) M12-ports

Delivery informations

Availability available

Product description

Description Managed IP 65 / IP 67 switch in accordance with IEEE 802.3, store-and-forward-switching, software layer 2 Basic, electrical Fast-Ethernet (10/100 MBit/s) M12-ports

Port type and quantity 9 ports in total; uplink ports: 10/100 BASE-TX, M12 "D"-coding, 4-pole; 9 x 10/100 BASE-TX; TP-cable, auto-crossing, auto-negotiation, auto-polarity.

Type OCTOPUS OS20-000900T5T5TAFBHH

Order No. 942 025-005

More Interfaces

Power supply/signaling contact 1 x M12 5-pin connector, A coding,

V.24 interface 1 x M12 4-pin connector, A coding

USB interface n/a

Network size - length of cable

Twisted pair (TP) 0 - 100 m

Network size - cascading

Line - / star topology any

Ring structure (HIPER-Ring) quantity switches 50 (reconfiguration time < 0.3 sec.)

Power requirements

Operating voltage DC 24/36/48 VDC -60% / +25% (9,6..60 VDC)

Power consumption 6.7 W

Current consumption at 24 V DC 250 mA

Current consumption at 48 V DC 140 mA

Software

Management Serial interface V.24 web-interface, Telnet, SSHv2, HTTP, HTTPS, TFTP, SFTP, SNMP v1/v2/v3, Traps

Diagnostics LEDs (power 1, power 2, link status, data, redundancy manager, error) signalling contact, RMON (statistics, history, alarms, events), SysLog support, port mirroring

Configuration Command Line Interface (CLI), auto-configuration adapter, TELNET, BootP, DHCP Option 82, HiDiscovery

Security SNMP V3 (no encryption)

Redundancy functions redundant power supply

Other services 4 QoS queues, user priority (IEEE 802.1D/p), multicast support (IGMP Snooping/Querier)

Ambient conditions

Operating temperature -40 °C ... 70 °C

Storage/transport temperature -40 °C ... 85 °C

Relative humidity (also condensing) 10 % ... 100 %

MTBF 31.6 years; MIL-HDBK 217F; Gb 25 °C

Mechanical construction

Dimensions (W x H x D) 184 mm x 189 mm x 70 mm

Mounting Wall mounting

Weight 1300 g

Protection class IP65, IP67



Industrial Ethernet: Waterproof IP67/IP54 Switches: OpenOCTOPUS: OpenOCTOPUS Fast Ethernet

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49850-351255-400977/en/OS20-000900T5T5TAFBHH08.0/uistate>

Mechanical stability

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	20 V/m (80-3000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 2 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)

EMC emitted immunity

FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A

Approvals

Basis Standard	CE, C-Tick
Safety of industrial control equipment	GOST-R
Employment in vehicles	E1
Electronic mechanisms on rail-mounted vehicles	EN 50121-4, EN 50155, EN 45545, DIN 5510-2, NF F 16-101, NF F 16-102

Scope of delivery and accessories

Scope of delivery	M12-connector (ELWIK A 5012 PG7) for power connection, description and operating instructions
Note	Please note that some recommended accessory parts only support a temperature range from -25 °C to +70 °C and might limit the possible operating conditions for the entire system.
Accessories to order separately	M12 connector, "D"-coded (934 445-001); 2 m cordset with M12-connector, "D"-coded (934 578-001); 5 m cordset with M12-connectors, "D"-coded (934 578-002); 10 m cordset with M12-connectors, "D"-coded (934 578-003); Bulkhead M12 "D"-coded to RJ45 (934 498-001); OCTOPUS dust cover set (25 pieces) (942 057-001).OCTOPUS terminalcable (943 902-001), Autokonfigurationsadapter ACA11-M12 (EEC) (943 972-001)

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.