




Product information OpenOCTOPUS Gigabit Ethernet PoE - OCTOPUS OS32-0816020606TPEPHH

Industrial Ethernet:Waterproof IP67/IP54 Switches:OpenOCTOPUS:OpenOCTOPUS Gigabit Ethernet PoE

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49850-351255-400980/en/OS32-0816020606TPEPHH08.0/uistate>

Name	OpenOCTOPUS Gigabit Ethernet PoE
	
	Managed IP 65 / IP 67 switch in accordance with IEEE 802.3, store-and-forward-switching, software layer 2 Professional, Fast-Ethernet (10/100 MBit/s) and Gigabit-Ethernet (1000 MBit/s) ports, power sourcing equipment in accordance with IEEE 802.3af (PoE inline power), electrical Fast-Ethernet (10/100 MBit/s) and Gigabit-Ethernet (1000 Mbit/s) SFP-slots in accordance with IEC 63076-3-106, Version 1
Delivery informations	
Availability	available
Product description	
Description	Managed IP 65 / IP 67 switch in accordance with IEEE 802.3, store-and-forward-switching, software layer 2 Professional, Fast-Ethernet (10/100 MBit/s) and Gigabit-Ethernet (1000 MBit/s) ports, power sourcing equipment in accordance with IEEE 802.3af (PoE inline power), electrical Fast-Ethernet (10/100 MBit/s) and Gigabit-Ethernet (1000 Mbit/s) SFP-slots in accordance with IEC 63076-3-106, Version 1
Port type and quantity	18 ports in total; uplink ports: 1000 BASE-SFP-slots acc. IEC 63076-3-106, Version 1; 16 x 10/100 BASE-TX, thereof 8 x 10/100 BASE-TX PoE (phantom power); TP-cable, auto-crossing, auto-negotiation, auto-polarity.
Type	OCTOPUS OS32-0816020606TPEPHH
Order No.	942 069-003
More Interfaces	
Power supply/signaling contact	1 x M12 5-pin connector, A coding, 1 x M12 5-pin connector, A coding
V.24 interface	1 x M12 4-pin connector, A coding
USB interface	1 x M12 5-pin socket, A coding
Network size - length of cable	
Twisted pair (TP)	0 - 100 m
Multimode fiber (MM) 50/125 µm	see SFP LWL-Modul M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 µm	see SFP LWL-Modul M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM) 9/125 µm	see SFP LWL-Modul M-SFP-LX/LC
Network size - cascadiability	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0.3 sec.)
Power requirements	
Operating voltage DC	48 VDC (46 .. 57 VDC)
Power consumption	146 W
Current consumption at 48 V DC	3000 mA
Software	
Management	Serial interface V.24 web-interface, Telnet, SSHv2, HTTP, HTTPS, TFTP, SFTP, SNMP v1/v2/v3, Traps
Diagnostics	LEDs (power 1, power 2, link status, data, redundancy manager, error) cable tester, signalling contact, RMON (statistics, history, alarms, events), SysLog support, port mirroring
Configuration	Command Line Interface (CLI), auto-configuration adapter, TELNET, BootP, DHCP Option 82, HiDiscovery
Security	Port Security (IP and MAC), SNMPv3, SSHv3, SNMP access settings (VLAN/IP), IEEE 802.1X authentication
Redundancy functions	redundant power supply
Other services	4 QoS queues, user priority (IEEE 802.1D/p), VLAN (IEEE 802.1Q), unknown multicast filtering, multicast support (IGMP Snooping/Querier, GMRP), broadcast limiter per port, ingress and egress packet limiter, Flow Control IEEE 802.3x, LLDP (topology discovery IEEE 802.1AB), Link Aggregation (IEEE 802.3ad), buffered real-time clock, PTP support (Precision Time Protocol) (IEEE 1588 client for system clock only), SNTP support (Simple Network Time Protocol, client/server)
Ambient conditions	
Operating temperature	-40 °C ... 70 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (also condensing)	10 % ... 100 %



Industrial Ethernet: Waterproof IP67/IP54 Switches: OpenOCTOPUS: OpenOCTOPUS Gigabit Ethernet PoE

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49850-351255-400980/en/OS32-0816020606TPEPH08.0/uistate>

MTBF	44 years; Telcordia, Gb 25 °C
Mechanical construction	
Dimensions (W x H x D)	338 mm x 189 mm x 70 mm
Mounting	Wall mounting
Weight	2700 g
Protection class	IP65, IP67
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	20 V/m (80-3000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 2 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Basis Standard	CE, C-Tick
Safety of industrial control equipment	GOST-R
Electronic mechanisms on rail-mounted vehicles	EN 50155
Scope of delivery and accessories	
Scope of delivery	M12-connector (ELWIKA 5012 PG7) for power connection, description and operating instructions
Accessories to order separately	M12 connector, "D"-coded (934 445-001); 2 m cordset with M12-connector, "D"-coded (934 578-001); 5 m cordset with M12-connectors, "D"-coded (934 578-002); 10 m cordset with M12-connectors, "D"-coded (934 578-003); Bulkhead M12 "D"-coded to RJ45 (934 498-001); OCTOPUS dust cover set (25 pieces) (942 057-001). Fast Ethernet SFP-Transceiver: M-FAST SFP-MM/LC EEC (943 945-001), M-FAST SFP-SM/LC EEC (943 946-001), M-FAST SFP-SM+/LC EEC (943 947-001), M-FAST SFP-LH / LC EEC (943 948-001); Gigabit Ethernet SFP-Transceiver: M-SFP-SX / LC EEC (943 896-001), M-SFP-LX / LC EEC (943 897-001), M-SFP-LH / LC EEC (943 898-001), OCTOPUS terminal cable (943 902-001), Autokonfigurationsadapter ACA21-M12 EEC (943 913-002)

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.