




## Product information SPIDER II 8TX/2FX-SM EEC

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER II 8TX/2FX-SM EEC

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49855-50103-40587/en/conf/ui/istate>

Name	SPIDER II 8TX/2FX-SM EEC
	
	Entry Level Industrial ETHERNET Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Entry Level Industrial ETHERNET Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
Port type and quantity	8 x 10/100BASE-TX, TP-cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity, 2 x 100BASE-FX, SM-cable, SC sockets
Type	SPIDER II 8TX/2FX-SM EEC
Order No.	943 958-231
<b>More interfaces</b>	
Power supply/signaling contact	1 plug-in terminal block, 3-pin, no signaling contact
<b>Network size - length of cable</b>	
Twisted pair (TP)	0 - 100 m
Multimode fiber (MM) 50/125 µm	n/a
Multimode fiber (MM) 62.5/125 µm	n/a
Single mode fiber (SM) 9/125 µm	0 - 32,5 km, 16 dB link budget at 1300 nm, A = 0,4 dB/km, 3 dB reserve, D = 3,5 ps/(nm x km)
Single mode fiber (LH) 9/125 µm (long haul transceiver)	n/a
<b>Network size - cascadiability</b>	
Line - / star topology	Any
<b>Power requirements</b>	
Operating voltage	DC 9.6 V - 32 V
Current consumption at 24 V DC	max. 330 mA
Power consumption	max. 8.4 W 28.7 Btu(IT)/h
<b>Service</b>	
Diagnostics	LEDs (power, link status, data, data rate)
<b>Redundancy</b>	
Redundancy functions	n/a
<b>Ambient conditions</b>	
Operating temperature	-40 °C to +70 °C
Storage/transport temperature	-40 °C to +85 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	839,560 hours; Telcordia SR-332; Gb 25°C
<b>Mechanical construction</b>	
Dimensions (W x H x D)	35 mm x 138mm x 121 mm
Mounting	DIN Rail 35 mm
Weight	260 g
Protection class	IP 30
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3,5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge



## Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER II 8TX/2FX-SM EEC

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49855-50103-40587/en/conf/ui/state>

EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (linie/earth), 1 kV (linie/line), 1 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 kHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
<b>Approvals</b>	
Safety of industrial control equipment	cUL 508
EMV regulations for assembly in vehicles	n/a
Employment in vehicles	E1
<b>Scope of delivery and accessories</b>	
Scope of delivery	Device, terminal block, operating manual
Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.