

RW-9921-101X

Product Data Sheet



RADWIN INDOOR UNITS

Ordering Info :

RW-9921-101X	PoE device 100BaseT/GbE interface for RADWIN HBS 5200 and RADWIN 2000 C Series radios , with AC power feeding (see note below)
---------------------	--

Note:

Replace X with a digit from the list according to AC plug type required:

- 1 – European AC plug
- 2 – US AC Plug
- 3 – UK AC Plug
- 4 – Indian AC Plug
- 5 – Australian AC Plug
- 6 – AC open connector
- 7 – Argentina AC Plug
- 8 – South Africa AC Plug

Examples: RW-9921-1011 for European AC plug, RW-9921-1014 for Indian AC plug.

RADWIN

RW-9921-101X - Product Specifications

ELECTRICAL	
AC Input Voltage	100-240VAC nominal, 90-264VAC max range
Input Frequency	47-63Hz
Input Current	2.0A (rms) 115VAC at Max. load 1.2A (rms) 230VAC at Max. load
Max. In-rush current	30A for115VAC at Max. load 60A for230VAC at Max. load
Standby Power	0.5W(Max)at240Vac
DC Output Voltage	56V
Protection	Short circuit protection Auto recovery Over voltage protection
Environmental	
Operating Temperatures	0°C - 40°C/32°F - 104°F
Humidity	90% non-condensing
Safety	
UL	60950
C-UL	60950
TUV/GS	IEC/EN 60950
EMC	
ESD	61000-4-2
RS	61000-4-3
EFT	61000-4-4
Surge	61000-4-5
CS	61000-4-6
DIPS	61000-4-11
EMI	FCC part 15 class B, CISPR Pub 22 class B
Mechanical	
Case	Plastic
Dimensions	163mm(L) x 65mm(W) x 36mm(H)
Weight	400g/0.88lb
Interfaces	
PoE output	RJ-45 connector
Ethernet input	RJ-45 connector
AC input on device	Standard socket IEC320 C14 type
AC cable	Variety of AC plugs available (see below)
Ethernet / ODU	RJ-45 connector

Corporate Headquarters, T. +972.3.766.2900, E. sales@radwin.com, www.radwin.com

The RADWIN name is a registered trademark of RADWIN Ltd.
© All rights reserved, March 2011 DS- RW-9921-101x/03.11

RADWIN