#### **RADWIN Accessories**

RW-9924-0006 Lightning Protector

**Product Data Spec** 



**RADWIN Accessories** 

### **Lightning Protector- RW-9924-0006**

RADWIN RW-9924-0006 is an external lightning protection unit supporting data and signal surge protection over PoE.

RADWIN RW-9924-0006 offers outdoor data line series protection designed to support Ethernet applications including 10/100 and 1000 BaseT interfaces with PoE.

RW-9924-0006 incorporates high-power gas discharge tube and current transistor protection in a single protector unit.

## **Product Highlights**

- Support data rates of up to 1000Mbps
- Enclosure rating of IP67 for all outdoor conditions
- Small form factor
- High data voltage protection
- Fast response with RADWIN ODU outdoor and indoor products
- Pole and Wall mounting kits
- Simple installations



# **RW-9924-0006 - Product Specifications**

Electrical	
Compatible Interfaces	10/100/1000BaseT
Data Rates	Up to 1000Mbps
Nominal Operational Voltage	48 VDC
Maximum Operational Voltage	60 VDC - 650 mA
Maximum Continues current	1 A
Impedance	90 to 110 Ohm
Connection type	RJ45 CAT5e STP (shielded)
Pin-out	8 wires + shielding
Pins Protected	All pins protected
Response time	<5 microseconds (with ODU)
Nominal discharge currents	
Line to Line	500 A @ 8/20μs
Line to Ground	2000 A @ 8/20 μs
Impulse Discharge Current	
20000 A, 8/20 μs	1 operation minimum
10000 A, 8/20 μs	> 10 operations
2000 A, 10/350 μs	1 operation
200 A, 10/1000 μs	> 300 operations
200 A, 10/700 μs	> 500 operations
Impulse Spark-over	
DC Spark-over ±20 % @ 100 V/s	150 V
100 V/μs	350 V
1000 V/μs	500 V
Capacitance	< 2 pF
DC Holdover Voltage	80V
Mechanical	
Enclosure	Metal
Connection to bonding Network	Screw
Dimensions	150mm
Weight	220 gram (0.22Kg)
Environmental	
Operating temperature	-40 to +60
Storage temperature	-50 to +70
Enclosure rating	IP67
Humidity	100% non condensing

#### **Ordering Info**

**Part Number:** RW-9924-0006

**Description:** External Lightning Protection Unit supporting 100BaseT and 1000BaseT interfaces and signal surge

protection over power over Ethernet (including 0.5m CAT5e cable and mounting kit)

