

Category 6 and 5e Dynamic Angle Right/Left Patch Panels



Back view with cable management bar

Specifications

Performance:	ANSI/TIA-568-C.2 Category 5e or 6, ISO 11801 Class D, E
Applications Supported:	10Base-T, 100Base-TX, 1000Base-T, E1, T1
Front Interface:	UTP RJ45
Rear Interface:	KRONE LSA-PLUS® (110 tool compatible)
Weight:	0.544 kg/1.2 lbs
Rack Mounting:	19" EIA
Safety:	UL, cUL, CE, EN 60950
Operating Temperature:	0° to 40° C (32° to 104° F)
Storage Temperature:	-20° to 70° C (-4° to 158° F)

Ordering Information

Description	Quantity	Dimensions (HxWxD)	Ordering Number
24-port Category 6 angle right/left patch panel, T568A/B compatible	1	44.45 mm x 482.6 mm x 38.1 mm (1.75" x 19" x 1.5")	PP24AC6T
48-port Category 6 angle right/left patch panel, T568A/B compatible	1	88.9 mm x 482.6 mm x 38.1 mm (3.5" x 19" x 1.5")	PP48AC6T
24-port Category 5e angle right/left patch panel, T568A/B compatible	1	44.45 mm x 482.6 mm x 38.1 mm (1.75" x 19" x 1.5")	PP24AC5ET
48-port Category 5e angle right/left patch panel, T568A/B compatible	1	88.9 mm x 482.6 mm x 38.1 mm (3.5" x 19" x 1.5")	PP48AC5ET
Rear cable management bar		44.45 mm x 482.6 mm x 101.6 mm (1.75" x 19" x 4")	ADCCMR-A
ID tabs (icons)	25 per bag		ADCICBXX*

*Replace XX with: 03 = Red 09 = Yellow 04 = Green 10 = Purple 05 = Blue 11 = Brown 08 = Orange



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2015 CommScope, Inc. All rights reserved.

KRONE, LSA-PLUS and all trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc.

This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-104563.3-AE (11/15)